

S688 Square Jaw Clamp Meter



FEATURES

Permalloy core excellent for leakage current detection
Clamp size: 88mmx88mm suitable conductor of various size
High resolution 0.01mA
Square jaw opening easy to fit in densely packed wires
Measurement Range: 0.00mA to 1000A



SPECIFICATIONS

Function	AC leakage current, current measurement
Measurement Range	0.01mA to 1000A (50/60Hz auto)
Power	6V DC (alkaline dry battery LR6×4, AA)
Test Method	Clamp CT, integration
Jaw size	88mm×88mm (φ88mm cable, or 96mm×4mm flat steel grounding)
Accuracy (26°C±3°C, below 70%RH)	0.00mA to 300A: ±1.5%±5dgt
	300A to 1000A: ±2%±5dgt
Data storage	99 groups, flashing "FULL" symbol indicates that the storage is full
Frequency	50Hz, 60Hz automatic
Range	Auto ranging
Sampling Rate	2 times/sec
Line Voltage	Below AC 600V
Display	4-digit LCD display

Dimensions	287mm×130mm×41mm
Data Hold	Data hold function: "HOLD" symbol display
Saved Data	Browse data function: Indicated by the "MR" symbol, you can browse the stored data
Automatic shut-down	After about 15 minutes of power on, the meter automatically shuts down to reduce battery consumption
Weight	Meter: 787g (including battery)



SALES OFFICE

Email: sales@eaglotest.com

Tel: +86 020 31529626

Add: Building 4, No.18 Keyuan Road,
Baiyun District, Guangzhou, Guangdong, China

S688 Square Jaw Clamp Meter

www.eaglotest.com
Eaglotest Technology