# S688 Square Jaw Clamp Meter

## FEATURES

| |
|---|
| Permalloy core excellent for leakage current detection |
| Clamp size: 88mmx88mm suitable conductor of various size |
| High resolution 0.01mA |
| Square jaw opening easy to fit in densely packed wires |
| Measurement Range: 0.00mA to 1000A |

## SPECIFICATIONS

| | |
|---|---|
| Function | AC leakage current, current measurement |
| Measurement Range | 0.01mA to 1000A (50/60Hz auto) |
| Power | 6V DC (alkaline dry battery LR6×4, AA) |
| Test Method | Clamp CT, integration |
| Jaw size | 88mm×88mm (φ88mm cable, or 96mm×4mm flat steel grounding) |
| Accuracy (26°C±3°C, below 70%RH) | 0.00mA to 100A: ±1.5%±5dgt |
| | 100A to 1000A: ±2%±5dgt |
| Data storage | 99 groups, flashing "FULL" symbol indicates that the storage is full |
| Frequency | 50Hz, 60Hz automatic |
| Range | Auto ranging |
| Sampling Rate | 2 times/sec |
| Line Voltage | Below AC 600V |
| Display | 4-digit LCD display |
| Working Temperature and Humidity | -10°C to 40°C,below 80% RH |
| Storage Temperature and Humidity | -10°C to 60°C,below 70% RH |

| | |
|---|---|
| Dimensions | 287mm×130mm×41mm |
| Data Hold | Data hold function: "HOLD" symbol display |
| Saved Data | Browse data function: Indicated by the "MR" symbol, you can browse the stored data |
| Automatic shut-down | After about 15 minutes of power on, the meter automatically shuts down to reduce battery consumption |
| Weight | Meter: 787g (including battery) |

**S688**
**Square Jaw Clamp Meter**

**SALES OFFICE**

Email: sales@eaglotest.com
Tel: +86 020 31529626
Add: Building 4, No.18 Keyuan Road,
Baiyun District, Guangzhou, Guangdong, China

www.eaglotest.com
Eaglotest Technology